



European Tractor Pulling Committee

Tech and Safety Board

Dennes Jansens (NL) etpcsit@gmail.com

Paul Tucker (GB) paultractor74@gmail.com

Willem Wempe (NL) willem.wempe@hetnet.nl

Mario de Wever (B) mdewever@vodafonehuis.nl

Peter de Wit (NL) etpc@hetnet.nl

Info season 2017

Rulebook updates season 2017:

1: Page 17 and 19 Chapter 2 D point 11 and 16i

11. All bell housings less than 10 mm thick (explosion area) must use a 4130 chrome molybdenum liner minimum 2,3 mm thick. Inner diameter of clutch protection not more than 50 mm. larger than flywheel/clutch combination outer diameter.
- 16 i. Liners in aluminium bell-housing , following options possible:
- a- using 2 liners: second additional liner same material and thickness as the OEM liner delivered with the OEM belhousing.
 - b- using 2 liners: second additional liner steel or titanium min. 2mm. thick with a min. tensile strength, ultimate Rm 670 Mpa and a min. elongation at break of 10%.
 - c- using one (1) liner steel or titanium min. 4 mm. thick with a min. tensile strength, ultimate Rm 670 Mpa and a min. elongation at break of 10%.
 - d- using one (1) OEM liner and a ETPC approved clutch-blanket around the bellhousing.

2: Page 25 Chapter 2 H point H2

2. All tractors shall have wide front axles. Front wheels shall track with the rear wheels.

All pulling vehicles (except Trucks) must have skid plates under the front axle to keep vehicle on the track in case of losing a front wheel.

Skid plates must be one of the two types listed below:

- Skid plate mounted in line with each frame rail (on both sides) at the center of the front axle equal in strength to frame rail material.
Skid plate surface to be a min. of 100 mm wide and 300 mm long with a min. 150 mm curve measured from the front most part of rolled edge.
(0.95 t mods: min. 50 mm wide ,min. 250 mm length and min. 50 mm curve)
- Skid plate mounted to center of axle, must be a min. of 300 mm wide with rolled edge front. Plate must be min. 200 mm length.
(0.05 mods : min. 250 mm wide with rolled edge front and min.100 mm length.)

Skids must be securely mounted and braced to the chassis/front axle.

Skids must be able to support the weight of the front end when checked with a jack.

Maximum ground clearance is from the bottom of the wheel rim to the ground, not to exceed 100mm (0.95 mods 50mm) with front tires in normal operating position.

Address of the Tech and Safety Board:
c/o Peter de Wit (mail:etpc@hetnet.nl)
Voorschoten
The Netherlands

E mail: etpc-ts@tractorpulling.com
Website: www.tractorpulling.com



European Tractor Pulling Committee

Tech and Safety Board

Dennes Jansens (NL) etpcsit@gmail.com

Paul Tucker (GB) paultractor74@gmail.com

Willem Wempe (NL) willem.wempe@hetnet.nl

Mario de Wever (B) mdewever@vodafonehuis.nl

Peter de Wit (NL) etpc@hetnet.nl

3: Page 44 Chapter 2N point 2

2. All pulling vehicles must be equipped with a fire extinguisher or firestick fully charged, in working condition and in easy reach of driver. Fire extinguisher/firestick must meet following requirements:
 - must be according DIN/EN 3 norm
 - must have CE conformation
 - must show expiry date
 - min. fire fighting time 8 seconds
 - must be manufacturer approved for use outside under windy conditions
 - powder extinguisher must be checked yearly [with certificate]
 - all other fire extinguishers must have a pressure gauge to check charged condition and have an age limit of max. 5 years.

4: Page 58/59 Chapter 4D Pro Stock point 4 and 6

4.

Engine cylinder head(s) must be OEM agricultural type for that brand engine as fitted in serial production in combination with the original engine block – no mixing of brand, or series of the brand.

There must be a minimum of 150 units produced with this engine block and cylinder head(s) combination and replacement cylinder head(s) used must be available under the part number from the manufacturer of that engine brand as listed in the original parts catalogue for that particular engine. If the brand no longer manufactures that cylinder head(s) and an alternative supplier now produces them these are acceptable as long as they are approved as a 'true' replacement copy by the original brand manufacturer and conform to all other rules.

For all engines designed as 'water cooled' within the cylinder head system the original water channels must be present as per the original production cylinder head(s) casting used in serial production. The original cylinder head(s) must be able to fit and work with the standard agricultural tractor engine as intended in normal daily use within agriculture – operationally not just functionally (i.e. must continue to work continuously over a number of hours). 'Air cooled' cylinder head(s) must be as per original serial production casting.

No recasting of cylinder head(s). Recasting will be defined as the process of manufacturing with an alternative mould/template to the one used in serial production.

Aftermarket machining and modifications allowed on the cylinder head(s) casting. No alterations to the casting allowed that will alter the original air inlet and outlet positions or bolt pattern. Bolt pattern head to block must be as original.

Connection side of inlet and exhaust manifolds must be 90 degrees with head gasket or OEM.

If there is any question of legality of cylinder head(s) it is up to the team to prove that the engine block and cylinder head combination is legal. If it cannot be confirmed that it is a legal combination ETPC will enforce the maximum penalty of a 1 year and 10 days ban for that tractor and team.



European Tractor Pulling Committee

Tech and Safety Board

Dennes Jansens (NL) etpcsit@gmail.com

Paul Tucker (GB) paultractor74@gmail.com

Willem Wempe (NL) willem.wempe@hetnet.nl

Mario de Wever (B) mdewever@vodafonehuis.nl

Peter de Wit (NL) etpc@hetnet.nl

6.

The use of a Common Rail diesel fuel system is permitted under the following criteria and specifications:

- must use a dual throttle position sensor output circuit.(circuit 1 ramps up ,circuit 2 ramps down)
- single throttle-circuit not allowed
- must use 2 springs to return throttle to idle.
- kill switch must interrupt the permanent current (30) and the current by ignition (15) to the ECU (engine control unit).
- kill switch must work according the fail-safe principle, activated when the electrical system is interrupted.
- kill switch must also activate the air shut-off as required on all diesel engines.(see chapter 2M kill switches, point 7).
- must have a fuel shut off valve control in the low pressure line towards the high-pressure pump and as close as possible to the high-pressure pump with control in easy reach of driver.



European Tractor Pulling Committee

Tech and Safety Board

Dennes Jansens (NL) etpcsit@gmail.com

Paul Tucker (GB) paultractor74@gmail.com

Willem Wempe (NL) willem.wempe@hetnet.nl

Mario de Wever (B) mdewever@vodafonehuis.nl

Peter de Wit (NL) etpc@hetnet.nl

Competition rules updates:

1: Season 2017 engine limits and weight compensation system

ETPC rulebook: Chapter 12 Engine limits:

Weight compensation system:

A- all engines will keep the same number of points that they currently have, and all classes will maintain the current limits as in Chapter 12-B of the current ETPC rulebook.

B- the base weight of the Heavy Modified class will be 4.2 ton

C- a weight compensation factor will be introduced for engine configurations which are not close to the maximum engine limits.

Giving tractors with lower engine points extra weight, as follows:

2.5 t. modified (new: **Light Modified**) max. engine points 42.

- 38-42 eng. points: 0 kg extra weight allowed
- 33-37 eng. points: 100 kg extra weight allowed
- 32 or less eng. points: 200 kg extra weight allowed

3.5 t. modified (new: **Modified**) max. engine points 57.

- 53-57 eng. points: 0 kg extra weight allowed
- 48-52 eng. points: 100 kg extra weight allowed
- 47 or less eng. points: 200 kg extra weight allowed

Address of the Tech and Safety Board:
c/o Peter de Wit (mail:etpc@hetnet.nl)
Voorschoten
The Netherlands

E mail: etpc-ts@tractorpulling.com
Website: www.tractorpulling.com



European Tractor Pulling Committee

Tech and Safety Board

Dennes Jansens (NL) etpcsit@gmail.com

Paul Tucker (GB) paultractor74@gmail.com

Willem Wempe (NL) willem.wempe@hetnet.nl

Mario de Wever (B) mdewever@vodafonehuis.nl

Peter de Wit (NL) etpc@hetnet.nl

4.2 t. modified (new: **Heavy Modified**) max. engine points 76

- No extra weight allowed

Additional rules to this weight compensation:

- All tractors with only automotive V8 engines falling under point 1 B and 1 C in the engine limit system not allowed to add any weight.
- Engine configuration and weight can not be changed during the whole season, except with written permission of the ETPC board.
- Tractors equipped with only naturally aspirated engines receive max. compensation in weight.
- ETPC can change compensation weight / points thresholds and blower overdrive on a yearly basis

2: Diesel Super Stock tractors: allowed 300kg extra weight (max. weight 3800 kg)